

## Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.







### General Information

Ambient	-20°C to 40°C
Temperature	
Range (°C)	
IP Rating	IP20
Nominal	15,000 h
Lifetime (h)	
Protection	Class II
Rating	
Installation	Internal
Area	

# Vintage Filament Candle (Dim)

VC4.2D-ES25 07733

## Vintage Filament Candle 4.2W Dimmable ES (E27) 2500K gold

- Special coating with a gold finish gives an antique appearance
- Linear LED filament provides a traditional appearance
- Creates a warm and cosy living space
- Even light distribution
- Save energy up to 90% compared with an incandescent filament lamp



Technical Summary		
Product Code	VC4.2D-ES25	
Input Voltage Supply	220-240Vac 50/60Hz	
Inrush Current (peak/duration) (A)	3.6A/1440us	
Default Power	4.2 W	
Power Factor	0.4	
Default CCT	2,500 K	
SDCM of CCT	<6	
CRI	80	
Dimmable	Y	
Flicker	<10%	
Lumens Output Maximum	450 lm	
Maximum Efficiency	112 lm/W	
L70B50 Lifetime (h) @Ta 25 °C	15,000 h	
L80B10 Lifetime (h) @Ta 25 °C	15,000 h	
L90B10 Lifetime (h) @Ta 25 °C	5,000 h	
Nominal Lifetime (h)	15,000 h	
Blue Light Hazard	RG1	
Weight	0.02Kg	
Dimensions (L x W x D) (mm)	94x⊘35	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com
















## Vintage Filament Candle (Dim)

07733 VC4.2D-ES25

## Overview

The Kosnic LED Filament lamp has a traditional appearance and gives an even spread of light in all directions. It is also highly functional and efficient. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.







### General Information

Ambient -20°C to 40°C Temperature Range (°C)  IP Rating IP20 Nominal 15,000 h Lifetime (h) Protection Class II Rating Installation Internal Area		
Range (°C)  IP Rating IP20  Nominal 15,000 h  Lifetime (h)  Protection Class II  Rating  Installation Internal	Ambient	-20°C to 40°C
IP Rating IP20 Nominal 15,000 h Lifetime (h) Protection Class II Rating Installation Internal	Temperature	
Nominal 15,000 h Lifetime (h) Protection Class II Rating Installation Internal	Range (°C)	
Lifetime (h)  Protection Class II  Rating  Installation Internal	IP Rating	IP20
Protection Class II Rating Installation Internal	Nominal	15,000 h
Rating Installation Internal	Lifetime (h)	
Installation Internal	Protection	Class II
	Rating	
Area	Installation	Internal
	Area	

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com













Kosnic Lighting Kosnic UK Kosnic Lighting UK Kosnic UK